场地尺度绿色基础设施的协同设计

——以咸阳渭柳湿地公园生态修复设计为例

COLLABORATIVE DESIGN OF SITE-SCALE GREEN INFRASTRUCTURE:
A CASE STUDY ON THE ECOLOGICAL RESTORATION DESIGN OF WEILIU WETLAND PARK IN XIANYANG

<https://doi.org/10.15302/J-LAF-20170503>
收稿时间 RECEIVED DATE / 2017-06-19
中图分类号 / TU986
文献标识码 / A

栾博

北京大学环境科学与工程
学院博士研究生，北
京大学深圳研究生院绿
色基础设施研究所执行
所长

王鑫

北京一方天地环境景观
规划设计咨询有限公司
总经理、高级工程师，
北京大学深圳研究生院
绿色基础设施研究所副
所长

金越延

北京一方天地环境景观
规划设计咨询有限公司
主创设计师

柴民伟

北京大学深圳研究生院
博士，高级工程师

胡春明

中国科学院生态环境研究
中心博士，高级工程师

Bo LUAN

PhD Candidate of College
of Environmental Sciences
and Engineering, Peking
University; Executive
Director of Green
Infrastructure Institute
of Peking University
Shenzhen Graduate School

Xin WANG

Manager and Senior
Engineer at Yifang
Ecoscape Consulting
Studio; Deputy Director
of Green Infrastructure
Institute of Peking
University Shenzhen
Graduate School

Yueyan JIN

Senior Designer at Yifang
Ecoscape Consulting
Studio

Minwei CHAI

PhD of Peking University
Shenzhen Graduate
School; Senior Engineer

Chunming HU

PhD of Research Center
for Eco-Environmental
Sciences, Chinese
Academy of Sciences;
Senior Engineer

整理 田乐
译 田乐 董帅 黄延锋
EDITED BY Tina TIAN
TRANSLATED BY Tina TIAN Clarie DONG Yanfeng HUANG

摘要

绿色基础设施是一种具有多重目标的综合性实践。在中国，由于缺少科学研究、工程技术、空间设计的多专业协同设计方法，大量绿色基础设施的场地实践目标单一，无法兼顾生态效益与人居环境品质，甚至造成生态损害。本文以陕西省咸阳市渭柳湿地公园项目的设计过程为例，探索了以科学分析评价为依据、以专业工程技术为支持，通过空间设计进行综合统筹的协同设计方法，以实现场地尺度绿色基础设施的综合价值。该方法对融合了科学性、技术性和艺术性的绿色基础设施场地实践具有借鉴价值。

关键词

绿色基础设施；海绵城市；生态修复；废水资源化；协同设计；渭河

ABSTRACT

Green Infrastructure (GI) is to integrate with multiple objectives into a comprehensive consideration. In China, the lack of multi-disciplinary collaborative design method combining research, engineering technology, and spatial design as a whole limits the practice of GI, resulting in lots of single-function projects, unhelpful in the improvement of both urban resilience and the quality of city life. Taking the design process of Xianyang Weiliu Wetland Park as an example, this paper examines the collaborative design of multi-functional site-scale GI that is generated through a combination of scientific analysis and evaluation, engineering techniques, and landscape and spatial design, hoping to provide reference for the design and practice of GI-based ecological restoration and urban renewal in China.

KEY WORDS

Green Infrastructure; Sponge City; Ecological Restoration; Wastewater Reutilization; Collaborative Design; Weihe River

026

VOLUME 5 / ISSUE 5 / OCTOBER 2017

1 引言

绿色基础设施是一个跨尺度、多层次、相互连接的基础性绿色空间网络，是能够提供综合生态系统服务的多目标系统性工程^{[1]-[7]}。近年来，我国大量开展以海绵城市建设、黑臭水体治理、河道生态综合治理为代表的绿色基础设施实践，但由于设计过程缺乏专业协同性，不少项目无法兼顾多元目标和功能，以致难以达到绿色基础设施的标准。究其原因，一方面，由环境工程、市政工程或水利工程等专业主导的绿色工程往往强调技术性，专注解决单目标问题，缺乏对人居环境综合价值的提升；另一方面，由景观设计专业主导的实践重在营建人居环境空间品质，但因缺乏工程专业技术的支持，致使项目建成后的生态效益不显著，甚至成为“生态花瓶”，造成资源浪费和生态损害^{[1][8][9]}。

目前，一些中国学者对公共空间、建筑的协同设计进行了相关研究^{[10]-[12]}，但对于绿色基础设施的协同设计研究不足。并且，对于绿色基础设施的宏观规划方法讨论较多^{[13]-[21]}，而对场地尺度的设计方法探索较少。不同于一般的园林和公共空间设计，场地尺度绿色基础设施设计的综合性与系统性更要求其运用协同工作方法，包括市政、水利、环境、生态、景观、建筑等专业的横向协作，以及科学研究、工程技术与空间设计等领域的纵向合作。本文以咸阳渭柳湿地公园设计为例，探讨如何将研究分析的科学性，环境、水利、生态、市政等专业工程的技术性与人居环境设计的艺术性统筹落实于场地空间实践中。

2 项目概况

自古以来，关中地区就有“八水绕长安”之景象，作为其中的主河流，渭河是西安和咸阳的母亲河，其对于关中地区的生态基础至关重要（图1）。设计场地位于渭河流经咸阳市渭城区的自然洪泛滩地上，占地面积约125hm²，西起咸阳—陇海铁路桥，东至上林大桥，北接渭河防洪大堤（百年一遇标准），南至渭河主河槽（图2）。在快速城镇化背景下，传统的水利工程处理方式和城市美化运动破坏了紧邻

1 Introduction

Green Infrastructure (GI) is a type of fundamental green space network of multiple scales and various levels, in which the components are inter-connected, providing comprehensive ecosystem services^{[1]-[7]}. In recent years, the GI practice in China, represented by sponge city construction and river restoration, has been greatly promoted. However, largely because of the lack of multi-disciplinary collaboration, many of them are low-quality single-function projects. On one hand, most green engineering projects highly rely on technological support of environmental engineering, municipal engineering, and hydraulic engineering, and often focus on dealing with certain problems, paying less attention to spatial design and place making; on the other hand, in most practices led by professionals of landscape architecture, spatial and ecological design of the site is prioritized while lacking engineering support, resulting in built projects with poor ecological performance, or even worse, causing resource wastage and damage to local ecosystems^{[1][8][9]}.

Collaborative design on public space and architecture has been widely studied in China^{[10]-[12]}, but relative research on GI is rarely conducted. In addition, most existing research focuses on macro-scale GI planning^{[13]-[21]}, while the site-scale design approach is less studied. Different from the general public space design, the complexity of site-scale GI requires a broader inter-disciplinary collaboration between civil engineering, hydraulic engineering, environmental science, ecology, architecture, and landscape architecture, and a closer collaboration between research, engineering technology of construction, and spatial design. Taking Xianyang Weiliu Wetland Park as an example, this paper reviews the process of how to integrate research, engineering technology, and aesthetics into a comprehensive design.

2 Background

There has been a scene in Weihe Plain where eight rivers ran around Chang'an since the Tang Dynasty, amongst which Weihe River is the mother river of the cities of Xi'an and Xianyang, and is vital to the regional ecosystem (Fig. 1). The site is located on a natural floodplain in Weicheng District of Xianyang City, where Weihe River runs through, covering an area of 125 hm², reaching north to the Weihe Levee (withstanding 100-year flood events) and south to the main canal of Weihe River, with the Xianyang-Longhai Railway Bridge in the west and the Shanglin Bridge in the east (Fig. 2). The natural floodplain was dramatically changed by the rapid urban construction, especially

场地的上下游自然河滩的生态原貌，使渭河滩地丧失了应有的综合生态系统服务功能，且消耗了大量资源，甚至造成了环境负担。本案例场地成为了为数不多得以保留下来的自然泛洪漫滩。

场地临城市部分地势较高，大部分地块曾用作为苗圃基地，其余部分被市民自发开垦为菜园和藕塘；临渭河部分是地势较低的河漫滩，无序取土造成了大量采砂坑。在河滩区域的北侧，长期的挖沙、堆填和洪水冲刷形成了若干陡坡（土坎）。场地中原有的河道控导工程（土堤）横贯东西，两侧现有数十棵长势良好的垂柳；多条南北向排水渠穿过场地，将雨污合流水排向渭河（图3）。

by grey infrastructures and ornamental man-made earthworks which disturbed the performance of the local ecosystems. Fortunately, the site was remained as one of the few natural floodplains in the region.

The north side of the site was of a higher elevation and most land was occupied as a nursery while other parcels being used as vegetable gardens and lotus ponds by the citizens. On the south, the lower side, there were many deep pits, caused by improper sand mining. Decades of years of earthwork and flooding shaped the north part of the floodplain into several abrupt slopes. The existing river course control infrastructure — basically several earth embankments — spanned throughout the site from east to west, with dozens of willows growing well. Several north-south drainage ditches cut through the site, discharging sewage and rainwater into the Weihe River (Fig. 3).

1. 场地区位图
 2. 场地周边用地性质分析
 3. 场地原貌
1. Site location
 2. Land use of the surroundings of the site
 3. Site photos before ecological restoration

3 协同设计方法

设计的总体思路是将本区段河滩作为重要的绿色基础设施，使其发挥综合性生态系统服务，包括消纳和蓄滞洪水、净化水体、提升生物多样性，以及提供丰富多样的休闲体验机会。而协同设计方法是实现多重目标的保障：首先，对场地进行定量与定性相结合的问题分析和诊断，随后将问题具体化、目标指标化；其次，基于各项指标分别交由各专业进行工程技术论证，并提出详细的技术方案；最后，通过空间设计统筹各专项技术，提出绿色基础设施的综合设计方案。

3.1 问题分析与诊断

本案例从生态安全格局、洪水淹没风险、水环境质量、土壤质量、生物多样性和居民使用情况等方面进行定量与定性相结合的分析评价，从而诊断场地中的目标问题和设计需达到的具体指标。

3.1.1 宏观生态格局分析

通过研究构建区域水系统、生物保护系统、文化遗产系统与休闲游憩系统，综合确定区域生态安全格局与宏观绿色基础设施网络，为该项目场地设计提供指导性定位。分析可知，项目所在的渭河自然河滩区段是西咸地区生态格局的重要组成部分，在洪水调节、水体净化、生物栖息地修复方面具有关键作用，也是渭河休闲廊道的重要组成部分。

3 Collaborative Design Methods

The overall design concept is to take the floodplain on the site as an important GI to provide ecosystem services, such as flood retention, water purification, biodiversity improvement, and opportunities for diverse recreational experience. Collaborative design methods were employed in this project to achieve these goals. First, quantitative and qualitative assessment and problem finding were applied in this research to inform and make objectives of restoration and improvement. Secondly, technique and engineering solutions were tested to develop detailed schemes. Lastly, a comprehensive plan was generated by integrating specific techniques with spatial and environmental design.

3.1 Assessment and Problem Finding

In the research, quantitative and qualitative analysis and assessment on the ecological security pattern, flood risk, water quality, soil health, biodiversity, and the usage by the local citizens were conducted in order to identify the problems and help make the objectives of restoration and improvement.

3.1.1 Analysis of Ecological Security Pattern at a Macro-scale

By studying and identifying the water system, biodiversity conservation system, cultural heritage system, and recreational system at a regional scale, an ecological security pattern and GI network were defined to provide guidance for the overall design of the site. The findings showed that the site, as a well preserved natural floodplain, was significant in the ecological security pattern of Weihe Basin, providing major services in flood retention, water purification, and habitat restoration, and improving the recreational service of Weihe River.

图 3-1-1 项目场地原貌

3.1.2 洪水淹没风险分析

设计区段属于渭河下游游荡性河段，对2000年、2005年、2008年和2014年的河势所进行的套绘分析表明渭河主河槽常年摆动不定（图4-1）。现有渭河大堤为100年一遇防洪标准，堤外河漫滩属本项目设计范围，此处场地因常年受洪水冲刷而存在不确定性。通过对本区段渭河的设计洪水推算和水面线推求（表1，2），并根据现状地势条件分析确定洪水淹没风险，可将场地分为三类风险区：被原控导工程（土堤）围护的高阶地（高程381~383m），可以抵御20年一遇的洪水侵袭；被土坎围护的中阶地（高程380~382m），可以抵御10年一遇的洪水侵袭；以及地势最低的自然滩地（高程374~381m），处于5年一遇洪水淹没范围（图4-2）。

表1: 设计洪水计算成果 (单位: m³/s)

Table 1: Flood Flows of Projected Recurrence Interval of Flood Events (m³/s)

洪水级别 Flood Frequency	100年一遇 100-year Flood	50年一遇 50-year Flood	20年一遇 20-year Flood	10年一遇 10-year Flood	5年一遇 5-year Flood
洪水流量 Flood Flows	9,700	8,570	7,080	5,910	4,710

表2: 设计洪水与水面线计算成果表 (单位: m)

Table 2: Flood Flows and Water Surface Profiles (m)

距西端起点 (陇海铁路桥) 距离 Distance from the Xianyang-Longhai Railway Bridge in the West	高程 Elevation	5年一遇洪水位 Water Level of a 5-year Flood Event	10年一遇洪水位 Water Level of a 10- year Flood Event	20年一遇洪水位 Water Level of a 20-year Flood Event
698	375.44	381.56	382.71	383.16
1,217	375.10	381.26	382.43	382.87
1,824	367.68	379.72	380.65	381.44
2,427	370.04	379.48	380.45	381.23
3,026	369.40	379.23	380.24	381.01

3.1.2 Assessment of Flood Risk

The site is located in a wandering reach at the lower Weihe River. The analysis on the river regime in the years of 2000, 2005, 2008, and 2014 indicated that the main course of Weihe River turned out to be unstable (Fig. 4-1). Although the existing Weihe Levee was built against 100-year flood events, the site covered the area outside the levee where there had been suffering from frequent floods in history. Based on the study on projected recurrence interval of flood events and water surface profiles of the site (Table 1, 2), low-, medium-, and high-flood risk zones were identified: 1) The high land protected by the earth embankments (elevation of 381 m to 383 m) where there

- 4-1. 2000年、2005年、2008年及2014年渭河河势套绘分析
- 4-2. 洪水淹没风险分析
5. 现场采样工作
- 4-1. Weihe River regimes of the year of 2000, 2005, 2008, and 2014.
- 4-2. Flooding risk zones
5. On-site sampling

3.1.3 水质污染分析

咸阳东郊污水处理厂的排放口位于场地西端，属本项目设计范围的上游区域。除污水处理厂排放口外，场地中还存在多条城市雨污排水明渠，造成了一定程度的水质污染问题。设计团队从排水明渠和排放口中选择了三个水样监测点，分别于2015年8月和2016年5月进行了水样采集和监测分析（图5）。水质分析结果如表3所示。

两次监测结果显示，污水处理厂排放口附近水位的总磷、总氮浓度均较高，低于地表水劣V类标准；而COD、氨氮可达到Ⅲ至Ⅳ类标准。而雨污明渠中水体的COD、氨氮、总氮、总磷的两次监测结果均较差，低于劣V类标准。总体上，污水处理厂排放尾水的水质均优于

could withstand 20-year flooding; the area protected by the abrupt slopes (elevation of 380 m to 382 m) where there could withstand 10-year flooding; the floodplain area (elevation of 374 m to 381 m) was in a risk of being inundated by 5-year flood events (Fig. 4-2).

3.1.3 Assessment of Water Quality

The East Xianyang Sewage Plant was located at the west end of the site, which discharged cleaned water into the upstream of the river section on the site. However, domestic sewage and rainwater was drained into the river via several uncovered ditches which caused water pollution problems. Water samples were collected from one of the drainage outlets of the Sewage Plant and two ditches in August 2015 and May 2016 (Fig. 5). The results of water pollution condition is shown in Table 3.

The two samplings both showed that the concentration of TP and TN of the water in the drainage outlets was high, indicating that the water quality was worse than the Surface Water Class V Standard; the concentration of COD and ammonia nitrogen were relatively low and the water quality met the Surface Water Class III or IV Standards. It was also

表3：水质监测结果（单位：mg/L）
Table 3: Results of Water Pollution Condition (mg/L)

	2015年8月 August 2015			2016年5月 May 2016		
样本采集点 Sampling Sites	污水厂排污口 A Drainage Outlet of Sewage Plant	雨污明渠1 No. 1 Ditch	雨污明渠2 No. 2 Ditch	污水厂排污口 A Drainage Outlet of Sewage Plant	雨污明渠1 No. 1 Ditch	雨污明渠2 No. 2 Ditch
总磷 TP	2.17	3.53	2.83	0.41	5.55	2.99
化学需氧量 COD	16.8	93.3	40.6	24.10	271	159
氨氮 NH	0.752	17.29	12.42	0.587	45.44	43.74
总氮 TN	4.07	28.5	19.8	15.60	42.2	46.40
镉 Cd	0.123	0.116	0.169	0.0025	0.0045	0.0038
铜 Cu	0.059	0.063	0.074	0.0142	0.0263	0.0114
锌 Zn	0.088	0.082	0.112	0.0316	0.1266	0.1371
铅 Pb	0.023	0.036	0.037	0.0178	0.0076	0.0089

注：2015年8月和2016年5月各采集一次，每次选择3个水样监测点；每个样点用500ml的塑料采集瓶采集两瓶样本，采样结果取平均值。
Note: Samplings were conducted in August 2015 and then in May 2016. Three sampling sites were selected in each time. All the water samples from each sampling site were collected with two 500 ml plastic bottles; the results were averaged.

两处雨污明渠。建议将雨污明渠中截留的污水引入污水处理厂，而后通过人工湿地进行进一步净化。

3.1.4 土壤质量分析

设计团队在渭河河滩设计区段选取了4种典型土地类型，对表层下0~5cm的土壤进行了采样分析，土壤监测结果与评价标准见表4。

结果显示，各取样点土壤中镉（Cd）、铜（Cu）、锌（Zn）、铅（Pb）和铬（Cr）元素含量均达到土壤一级标准，表明场地土壤未受到重金属污染。

3.1.5 生物多样性分析

（1）植物多样性

在场地的4种典型土地类型中，分别选取具有代表性的植物群落设置一个10m×10m的样方。在每个样方中随机选取三个1m×1m的小样方，进行植物多样性调查分析^[22]。12个植物样方的主要植物群落均为草本群落，种类分布及特征见表5。

经计算，4个样本采集点的Shannon–Wiener指数分别为：河岸农田（1.23）>农田周边土地（1.17）>河滩（0.98）>道旁空地（0.84）。河岸农田植物群落内部物种优势度和均匀性最低，而物种丰富度和物种多样性最高；农田周边土地的群落各指标均居于所有样点的中度水平；河滩受非法采砂和洪水冲刷影响，群落物种丰富度和多样性较

found that the concentration of COD, ammonia nitrogen, TN, and TP of the water in the ditches were quite high, indicating that the water was seriously polluted and worse than the Surface Water Class V Standard. The overall finding suggested that the quality of the cleaned water drained by the Plant was much better than the water in the ditches. Thus, in the design, the ditches were led into the Plant and a series of constructed wetlands were planned to be built to further purify the discharged water.

3.1.4 Assessment of Soil Health

Four typical soil types in the floodplain on the site were sampled (0 ~ 5 cm in depth) to assess the soil health. The results and assessment standards are shown in Table 4.

The results revealed that the element concentration of Cd, Cu, Zn, Pb, and Cr were low and met the Soil Class I Standard, indicating that the soil was not polluted by heavy metals.

3.1.5 Biodiversity Assessment

(1) Flora Diversity

Four typical soil types were sampled by studying one of the representative vegetation communities in each sampling site: three 1 m × 1 m quadrats were randomly chosen within a 10 m × 10 m area^[22]. Herb communities were mostly found in the 12 quadrats. The species distribution and characteristics are shown in Table 5.

The Shannon-Wiener index in the four sampling sites were: riverine farmland (1.23) > land surrounding farms (1.17) > floodplain (0.98) > roadside open land (0.84). Riverine farmland had the lowest species dominance and evenness, and the highest species richness and biodiversity. All the results of the land surrounding farms stayed at the medium level. Because of the damaging impact by sand mining and flooding, the richness and

表4：地表土壤监测结果与评价标准（单位：mg/kg）
Table 4: Heavy-metal Element Concentration Results and Assessment Standards (mg/kg)

		Cu	Zn	Pb	Cd	Cr
样本采集点 Sampling Sites	道旁空地 Roadside Open Land	18.80 ± 2.83	37.25 ± 8.27	10.93 ± 1.82	0.06 ± 0.05	34.20 ± 7.78
	河岸农田 Riverine Farmland	14.75 ± 0.92	22.45 ± 3.18	10.79 ± 2.23	0.02 ± 0.01	18.50 ± 1.27
	河滩 Floodplain	10.77 ± 1.08	13.00 ± 0.70	12.32 ± 1.25	0.01 ± 0.00	27.30 ± 1.84
	农田周边土地 Land Surrounding Farms	18.00 ± 0.42	31.40 ± 1.27	15.42 ± 0.35	0.11 ± 0.02	30.65 ± 0.07
土壤重金属元素含量评价标准 Assessment Standards of Heavy-metal Element Concentration	土壤一级标准 Soil Class I Standard	35	100	35	0.2	90
	陕西省土壤背景值 Soil Background Value in Shaanxi Province	20.1	66.1	20.9	0.0886	61.1

表5：植物种类分布特征 Table 5: Species Distribution and Characteristics												
	样方1 No. 1 Quadrat				样方2 No. 2 Quadrat				样方3 No. 3 Quadrat			
土壤类型 Soil Types	植物种 Species	密度 (株/m ²) Density (plant / m ²)	高度 Height (cm)	盖度 Coverage Ratio	植物种 Species	密度 (株/m ²) Density (plant / m ²)	高度 Height (cm)	盖度 Coverage Ratio	植物种 Species	密度 (株/m ²) Density (plant / m ²)	高度 Height (cm)	盖度 Coverage Ratio
河岸农田 Riverian Farmland	加拿大飞蓬 <i>Conyza canadensis</i> (L.) Cronq.	1	100	< 5%	莎草 <i>Cyperus rotundus</i> L.	61	30	45%	莎草 <i>Cyperus rotundus</i> L.	10	30	< 5%
	葎草 <i>Humulus scandens</i> [Lour.] Merr.	1	50	< 5%					马齿苋 <i>Portulaca oleracea</i> L.	6	15	60%
	驼绒藜 <i>Ceratoides latens</i> (J. F. Gmel.) Reveal et Holmgren	7	120	50%								
	芦苇 <i>Phragmites australis</i> (Cav.) Trin. ex Steud.	23	100	20%								
道旁空地 Roadside Open Land	驼绒藜 <i>Ceratoides latens</i> (J. F. Gmel.) Reveal et Holmgren	9	40	10%	驼绒藜 <i>Ceratoides latens</i> (J. F. Gmel.) Reveal et Holmgren	68	100	80%	驼绒藜 <i>Ceratoides latens</i> (J. F. Gmel.) Reveal et Holmgren	1	50	< 5%
	马唐 <i>Digitaria sanguinalis</i> (L.) Scop.	18	20	10%	马唐 <i>Digitaria sanguinalis</i> (L.) Scop.	135	30	15%	马唐 <i>Digitaria sanguinalis</i> (L.) Scop.	72	40	40%
	苘麻 <i>Abutilon theophrasti</i> Medicus	45	200	30%					加拿大飞蓬 <i>Conyza canadensis</i> (L.) Cronq.	15	110	40%
农田周边土地 Land Surrounding Farms	驼绒藜 <i>Ceratoides latens</i> (J. F. Gmel.) Reveal et Holmgren	13	170	90%	驼绒藜 <i>Ceratoides latens</i> (J. F. Gmel.) Reveal et Holmgren	72	100	80%	驼绒藜 <i>Ceratoides latens</i> (J. F. Gmel.) Reveal et Holmgren	5	50	< 5%
	马唐 <i>Digitaria sanguinalis</i> (L.) Scop.	15	100	10%	芦苇 <i>Phragmites australis</i> (Cav.) Trin. ex Steud.	42	150	40%	芦苇 <i>Phragmites australis</i> (Cav.) Trin. ex Steud.	4	170	10%
	无芒稗 <i>Echinochloa crusgalli</i> (L.) Beauv. var. mitis (Pursh) Peterm.	30	180	30%	钻形紫菀 <i>Aster subulatus</i> Michx.	2	70	< 5%	钻形紫菀 <i>Aster subulatus</i> Michx.	97	130	80%
									无芒稗 <i>Echinochloa crusgalli</i> (L.) Beauv. var. mitis (Pursh) Peterm.	4	160	< 5%
河滩 Floodplain	芦苇 <i>Phragmites Australia</i> (Cav.) Trin. ex Steud.	84	180	70%	加拿大飞蓬 <i>Conyza cana-densis</i> (L.) Cronq.	3	50	< 5%	加拿大飞蓬 <i>Conyza canadensis</i> (L.) Cronq.	65	120	30%
	钻形紫菀 <i>Aster subulatus</i> Michx.	90	120	40%	芦竹 <i>Arundo donax</i>	104	160	50%	钻形紫菀 <i>Aster subulatus</i> Michx.	31	80	10%
									芦竹 <i>Arundo donax</i>	1	60	< 5%

低；道旁空地受人为干扰影响较大，群落物种多样性最低。

（2）土壤动物多样性

在进行植物多样性调查的同时，在每个小样方（1m×1m）内采集植物凋落物下方20cm的土壤样品。利用光学显微镜、解剖镜、解剖器材，参考《生物多样性观测技术导则·大中型土壤动物》（HJ

biodiversity of the vegetation community on the floodplain were relatively low. The biodiversity of the roadside open land was the lowest due to the intensive disturbance by human activities.

(2) Microfauna Diversity

Soil samples were also randomly collected from the quadrats (1 m × 1 m, 20 cm in depth from the surface with decaying leaves cover). Tools including optical microscopes, anatomical lens, and other anatomical devices were used in the investigation. Referring to Guidelines on Biodiversity Observation, Large- and Medium-size Microfauna (HJ 710.10-2014)^[23], the found

710.10–2014)^[23]将采集的土壤动物标本鉴定到科或属（表6）。

表中可看出，三种土地类型中的昆虫和动物种类相似。河滩和农田周边土地的物种多样性和均匀度较高；道旁空地的昆虫和动物数量较多，且优势种明显。

3.1.6 居民使用情况分析

实地调研发现，附近居民在滩地自发开垦了大面积的养殖莲塘和菜地，反映出市民拥有强烈的使用和参与建议的意愿。但场地目前缺乏基本的服务设施，仅有渭河大堤边的简易步道和原控导工程（土堤）形成的土路可供散步，无法满足市民的亲水需求。

3.2 总体策略与设计目标

3.2.1 总体策略

设计团队基于上述6个方面的分析，提出了对案例场地的总体设计策略：

- 1）水安全层面：不同高程的场地面临着不同的洪水淹没风险，需构建适应性防洪体系，在保证防洪安全的前提下尽可能实现多重功能目标；
- 2）水环境层面：雨污水排放导致河滩水污染，需在城市与渭河间建立湿地净化缓冲带，以保证城市雨污水质提升后达标排放；
- 3）水资源层面：部分城市废水净化后可再生利用，作为植物灌溉和城市杂用水；
- 4）水生态层面：河滩区域受采砂等活动破坏，生态环境脆弱，生物多样性较低；设计方案建议修复多样化的滨水生物栖息地，并提高生物多样性；

microfauna species were identified (Table 6).

As shown in Table 6, the insect and animal species in the three sites were similar. The biodiversity and evenness in both floodplain and land surrounding farms were relatively high. The roadside open land had more insects and animals and a greater species dominance.

3.1.6 Usage by Local Citizens

In the floodplain area, extensive land was reclaimed into lotus pond and vegetable gardens by nearby residents which reflected their strong willingness to use the land and get engaged for its development. However, because of the lack of necessary amenities, only the trail along the Weihe Levee and the paths atop the earth embankments were accessible for people to have a walk. Thus, citizens’ recreational needs should be considered in the design.

3.2 Overall Strategies and Design Objectives

3.2.1 Overall Strategies

Overall strategies were developed based on the assessments of the project site, including:

- 1) Water security: as the elevation of the site varies, a flooding adaptive infrastructure system should be introduced in order to ensure the security of different flood risk zones and to provide multiple services.

表6：土壤动物种类及数量
Table 6: Species and Quantities of the Found Microfauna

道旁空地 Roadside Open Land			河滩 Floodplain			农田周边土地 Land Surrounding Farms		
昆虫种类 Species	昆虫数量 Quantity	所属目 Order	昆虫种类 Species	昆虫数量 Quantity	所属目 Order	昆虫种类 Species	昆虫数量 Quantity	所属目 Order
中华蚱蜢 <i>Acrida cinerea</i>	1	直翅目 Orthoptera	蚂蚁 Formicidae	2	鞘翅目 Coleoptera	蜘蛛 Araneida	2	蜘蛛目 Araneae
尺蛾幼虫 Geometridae	1	鳞翅目 Lepidoptera	蛱蝶 <i>Holotrichia diomphalia</i>	2	鞘翅目 Coleoptera	华北蝼蛄 <i>Gryllotalpa unispina</i>	1	直翅目 Orthoptera
蟠象 Pantatomidae	1	半翅目 Hemiptera	步甲 Carabidae	3	鞘翅目 Coleoptera	蛱蝶 <i>Holotrichia diomphalia</i>	2	鞘翅目 Coleoptera
叩甲 Elateridae	1	鞘翅目 Coleoptera	叶蝉幼虫 Cicadellidae	1	半翅目 Hemiptera	蚯蚓 Pheretima	4	单向蚓目 Haplotaxida
蜘蛛 Araneida	1	蜘蛛目 Araneae	蚯蚓 Pheretima	4	单向蚓目 Haplotaxida	鼠妇 <i>Porcellio</i>	6	等足目 Isopoda
步甲 Carabidae	3	鞘翅目 Coleoptera	蟠象 Pantatomidae	1	半翅目 Hemiptera	蚊 Culicidae	2	双翅目 Diptera
蜗牛 Fruticolidae	1	柄眼目 Stylomma-tophora	蜗牛 Fruticolidae	2	柄眼目 Stylomma-tophora	叩甲 Elateridae	1	鞘翅目 Coleoptera
鼠妇 <i>Porcellio</i>	28	等足目 Isopoda	蜘蛛 Araneida	1	蜘蛛目 Araneae	蜉蝣 Arachnoidea	7	蜉蝣目 Acarina

注：由于河岸农田受人类活动干扰较大，且沙质土壤干旱程度严重，未发现土壤动物分布，故未在本表中列出。
Note: None microfauna were found in the riverine farmland, because the ecosystem was strongly disturbed by human activities and the sandy soils were suffering from severe drought.

5) 水休闲层面：场地缺乏基本的服务与休闲设施，场地可达性与居民参与性较低；方案需构建丰富的休闲游憩系统，为市民提供可深度参与的多样化游憩机会。

3.2.2 分项设计目标

基于上述总体策略，方案提出了具体的设计目标（表7）。

3.3 专项技术方案

针对上述具体问题和各设计目标，环境、水利、生态、市政等专业技术团队分别对防洪、水质净化、生态修复等专项问题进行技术论证，提出合理的技术方案，以为空间设计综合决策提供专业技术支撑。

3.3.1 生态防洪技术

案例场地所在区段的渭河洪水冲刷流速为2~3m/s，可采用抛石、扦插、木桩、滩地覆绿等柔性生态防洪技术，分别对10年一遇和20年一遇淹没区的场地进行不同程度的保护，以构建适应性防洪措施。通过扦插活体木桩（柳枝）结合抛石的方式对原有土堤进行填筑改造，形成第一道生态护堤（可抵御10年一遇洪水侵袭），以对中阶地区形成有效保护。采用抛石的方式对原控导工程（土堤）进行改造，形成第二道生态护堤（可抵御20年一遇洪水侵袭），从而有效保护高阶地区。对于淹没风险最高的浅滩（5年一遇受淹区域），通过保护和修复自然岸线和滩地植被，例如补植芦苇（*Phragmites australis*）、菖蒲（*Acorus calamus*）等物种，可在泛洪时起到缓冲作用。

表7：具体设计目标
Table 7: Detailed Design Objectives

层面 Aspects	指标类别 Index	现状 Existing Condition	目标 Objectives
水安全 Water Security	洪水标准 Flood Adaptation	无 None	20年一遇和10年一遇的生态防洪 Against 20- and 10-year Flood Events
水环境 Water Environmental Health	水质 Water Quality	地表水劣V类 Surface Water Class V Standard	地表水IV类 Surface Water Class IV Standard
	土壤 Soil Health	一级 Soil Class I Standard	一级 Soil Class I Standard
水资源 Water Resource	废水资源化率 Waste Water Reuse Ratio	0	净化利用量占废水总排放量的10% The Amount of Purified and Reused Water Accounts for 10% of the Total Discharged Water
水生态 Riverine Ecosystem	生物多样性 (Shannon-Wiener指数) Biodiversity (Shannon-Wiener Index)	草本群落 Herbaceous Community [0.84 ~ 1.23]	提升 Increasing Biodiversity
		无木本群落 None of Trees Found	提升 Increasing Biodiversity
水休闲 Recreational System	游憩类型丰富度 Richness of Recreational Activity	低 Low	高 High
	可参与性 Citizen Participation	低 Low	高 High

2) Water environmental health: the existing water body was heavily polluted that made it necessary to create a wetland buffer between the city and the river which could purify rainwater and sewage before discharging into the river.

3) Water resource: after purification the waste water could be recycled for irrigation or domestic use.

4) Riverine ecosystem: the floodplain area was ecologically fragile and poor of biodiversity. The design should develop approaches for wetland habitat restoration and biodiversity enhancement.

5) Recreational system: the existing amenities and recreational facilities failed to meet local residents’ needs for accessibility and participation. It was necessary to build a leisure and recreational system where citizens could have diverse recreational experiences.

3.2.2 Detailed Design Objectives

Based on the overall strategies, detailed design objectives were generated (Table 7).

3.3 Specific Technique Proposals

Supported by the multi-disciplinary research of environmental science, hydraulic engineering, ecology and civil engineering, flood management, water purification, ecological restoration and other technique or engineering demonstrations were conducted to respond to specific problems on the site, further informing the design team to integrate technique and engineering schemes with spatial design.

3.3.1 Ecological Flood Management Techniques

The flood flow of the river in the project site was 2 ~ 3 m/s. Ecological flood management measures, such as riprapping, willow stake cutting, spiling, and covering bottomlands with green plants, were employed in the 10- and 20-year flood risk zones. The resilience of the medium-elevation land area was improved by cutting willow branches and riprapping on the earth embankments, forming the first ecological breakwater to withstand 10-year flood events. By using riprapping method in the high land area, a second ecological breakwater was created which could withstand 20-year flood events. In the design, the floodplain area (the area inundated by 5-year flood events) was planned as a buffer to attenuate the flood impact through natural shoreline protection and restoration, as well as by planting *Phragmites australias*, *Acorus calamus*, and other aquatic vegetation.

3.3.2 环境工程与人工湿地技术

为了降低城市雨污直接排入渭河所带来的水污染负荷,并将水质提升至地表水IV类标准,首先需将直排入渭河的劣V类雨污水截污收集至污水处理厂,再将污水厂尾水引入人工湿地进行净化。引入湿地的尾水水质需达到《城镇污水处理厂污染物排放标准》(GB18918—2002)^[24]一级A标准。

人工湿地的净化规模应满足绿化灌溉用水、生态景观用水和补充水体蒸发渗漏损耗的需水量,实现废水资源化利用。经计算,需灌溉绿化植被总面积按15hm²计。根据陕西省行业用水定额(DB61/T 943—2014),城市绿化用水定额为2.0L/m²·d,输水损耗按0.75计,因而绿化灌溉总需水量为400m³/d。为维持湿地与景观水体水质(面积约8hm²,平均水深1.0m),换水周期为10~15天,日换水量为5 333~8 000m³。根据咸阳地区蒸发量和土壤渗透系数,计算得出蒸发渗漏损耗平均约250m³/d。据此确定湿地净化能力需达到5 983~8 650m³/d。

根据净化规模和水质目标,确定了以潜流湿地为主、表流湿地为辅的人工湿地总体方案。由于人工湿地对磷的去除效率偏低,因此以总磷为计算指标^{[25][26]}。具体流程为:进水→垂直潜流湿地→氧化塘→水平潜流/表流湿地→兼性景观塘(图6)。其中,垂直潜流人工湿地系统承担主体净化功能,去除各类污染物,将进水中的总磷从0.5mg/L净化至0.25mg/L,同时创造厌氧、兼性环境,促进氮元素的反硝化;水平潜流、表流湿地的作用主要为进一步去除水体中的残留磷,并将总磷净化至0.2mg/L;表流湿地为好氧状态可促进氨氮的硝化反应;氧化塘能够发挥调蓄缓冲、水体复氧以及向下级均匀布水等功能(表8)。

磷在垂直潜流湿地的降解系数取0.3d⁻¹,停留时间取2.31天,湿地基质孔隙率取0.34,经计算,垂直潜流湿地深度需达1.8m,面积需3hm²。磷在表流湿地中的一级反应常数取12m/yr,经计算湿地面积需达5.4hm²。

3.3.3 生物栖息地修复技术

在基础环境方面:通过地形改造来营造多样化的栖息地类型。渭河阶地土质良好,局部区域利用现有高差,形成自然的起伏地形;对河滩现有采砂坑塘进行修复,种植湿生植物以形成起伏变化的河滩湿地。

在构建生态系统方面:通过构建植物种群和生物食物链,形成能够自我运转的生态系统。在保留滩地原有树木——主要为旱柳(*Salix matsudana*)和楝树(*Melia azedarach*)——的基础上,种植柿树(*Diospyros kaki*)、樱桃(*Cerasus pseudocerasus*)、杏树

3.3.2 Environmental Engineering and Constructed Wetland Technology

In order to reduce the water pollution load caused by the direct discharge of rainwater and domestic sewage into Weihe River, and to improve the water quality to meet the Surface Water Class IV Standard, the rainwater and sewage were collected and conveyed into the Plant, and when the quality of the cleaned water meet the Class A Standard of Municipal Wastewater Treatment Plant Discharge (GB18918-2002)^[24], it would flow into constructed wetlands for phyto-purification.

The purification capacity of the constructed wetlands was designed to meet the needs for on-site irrigation, ecological landscape maintenance, and evaporation and infiltration, maximizing the utilization of waste water. The total irrigation area of the site was estimated as 15 hm². According to industrial and domestic water consumption quota in Shaanxi Province (DB61/T 943-2014), the limit of water usage for urban green space is 2.0 L/m²d, and the loss coefficient is estimated as 0.75, so the total water consumption for green space irrigation is 400 m³/d. To maintain the water quality of wetlands and landscapes (the total area of water body is about 8 hm² with an average depth of 1.0 meter, which needs to be overall recharged every 10 to 15 days), a daily water consumption of 5,333 ~ 8,000 m³ is required. Estimated with the coefficient of evaporation and infiltration in Xianyang, a daily water consumption for on-site evaporation and infiltration is about 250 m³ on average. Hereby the daily purification capacity of the constructed wetland is required as 5, 983 ~ 8,650 m³.

According to the estimation of purification capacity and water quality improvement objective, the designed constructed wetlands mainly consist of subsurface flow wetlands, together with surface flow wetlands. TP is used as the indicator for phosphorus removal efficiency^{[25][26]}. The purification system consists of: vertical subsurface flow wetlands → retention ponds → horizontal subsurface flow wetlands and surface flow wetlands → facultative landscape ponds (Fig. 6). Vertical subsurface flow wetlands work as a major purification system which filtrate and remove pollutants, lowering the TP concentration from 0.5 mg/L to 0.25 mg/L and creating facultative anaerobe environment to promote nitrogen denitrification; secondly, residual phosphorus is further removed by horizontal subsurface flow wetlands and surface flow wetlands, reducing the TP concentration to 0.2 mg/L; surface flow wetlands provide aerobic environment for nitrification of ammonia nitrogen; retention ponds are created not only for oxidation, but also for flood retention, water reoxygenation, and dividing flows to lower levels. The whole process of phyto-purification is

6-1 人工湿地净化流程设计示意图

6-2 雨水净化系统

shown in Figure 8.

The phosphorus degradation coefficient in vertical subsurface flow wetland was 0.3 d^{-1} , with an average retention duration being 2.31 days, and porosity of wetland substrate being 0.34. It was estimated that the depth of vertical subsurface flow wetland should be no less than 1.8 meters, and the area should be 3 hm^2 at least. As the first-order reaction constant of phosphorus in surface flow wetland was 12 m/yr , a wetland area of 5.4 hm^2 was required.

3.3.3 Habitat Restoration Techniques

The general environment of the site could be improved by creating various habitats through landform design. The healthy soil of the terrace area of Weihe Basin benefited to the habitat creating, and natural landforms could be formed by taking advantage of the existing elevation difference in local areas; the sand mining pits on the floodplain were restored with moisture-resistant plants to create a dynamic undulating wetland.

By introducing plants and building food chains, the biodiversity of the site was improved and a self-sustaining

表8: 设计水质 (单位: mg/L)
Table 8: Objectives of Water Quality Improvement (mg/L)

水质指标 Water Quality Indicators	进水 Before Treatment	垂直潜流湿地出水 Purification Objective of Vertical Subsurface Flow Wetlands	水平潜流湿地出水 Purification Objective of Horizontal Subsurface Flow Wetlands
化学需氧量 COD	50	25	20
生物需氧量 BOD	10	6	4
氨氮 NH	5	2.0	1.5
总磷 TP	0.5	0.25	0.2
参考标准 Criterion	《城镇污水处理厂污染物排放标准》 (GB18918-2002) 一级A Class A Standard of Municipal Wastewater Treatment Plant Discharge	氨氮地表水Ⅴ类 其他地表水Ⅳ类 Ammoniacal Nitrogen Surface Water Class V Standard Other Surface Water Class IV Standard	氨氮地表水Ⅳ类 其他地表水Ⅲ类 Ammoniacal Nitrogen Surface Water Class IV Standard Other Surface Water Class III Standard

6-1. Diagram of the phytopurification process of constructed wetlands
6-2. Rainwater purification system

(*Armeniaca vulgaris*) 等可吸引鸟类的乔灌木, 并补植刺槐 (*Robinia pseudoacacia*)、桂花 (*Osmanthus fragrans*)、紫花苜蓿 (*Medicago sativa*) 等蜜源植物。保留场地原有的野生芦苇, 并种植荷花 (*Nelumbo nucifera*)、芦竹 (*Arundo donax*)、菖蒲 (*Acorus calamus*) 等乡土水生植物等, 以修复和营造水生动物、两栖动物和水禽的繁衍、觅食和庇护场所。

3.4 综合空间设计

将生态防洪技术、人工湿地技术、栖息地修复技术合理统筹于空间布局中, 通过空间设计途径最终形成集洪泛漫滩、海绵湿地、城市公园于一体的总体方案, 实现水安全、水环境、水资源、水生态、水休闲方面的综合目标 (图7, 8)。

3.4.1 与洪水过程相适应的空间布局

利用场地地势形成与洪水过程相适应的“一廊三层”的总体空间布局, 使市民使用程度与洪水安全等级相匹配。

1) 一廊是对现有土堤进行加固改造和景观修复后形成的贯穿东西的景观休闲绿廊, 高程381.30~383.10m, 能够抵御20年一遇的洪水侵袭;

2) 第一层为地势较高 (380.00~383.10m)、可承受20年一遇洪水 (7 080m³/s) 的景观休闲区。该区域受洪水淹没风险最低, 可为当地居民提供最为丰富的休闲活动服务, 包括绿道、亲水体验广场、秦腔文化广场、果园、市民农园、健身运动场、茶室、售货亭等功能设施。

3) 第二层为地势略低 (380.60~382.70m)、可承受10年一遇洪水 (5 910m³/s) 的生态湿地区, 主要功能包括废水净化和雨洪调蓄, 是城市与渭河之间的缓冲带, 兼顾休闲与环境体验功能, 包括栈道、垂钓、野餐等空间;

4) 第三层为地势较低 (374.00~381.00m)、受洪水淹没风险较高 (5年一遇标准以下) 的自然滩地区, 主要功能为保护和修复泛洪河滩

ecosystem was established. On the floodplain area, the existing trees, mostly *Salix matsudana* and *Melia azedarach*, were preserved, while introducing trees and shrubs which can provide foods or habitats for birds, such as *Diospyros kaki*, *Cerasus pseudocerasus*, and *Armeniaca vulgaris*, as well as nectar plants, such as *Robinia pseudoacacia*, *Osmanthus fragrans*, and *Medicago sativa*. The existing reeds in the site were remained and some aquatic plants were introduced, including *Nelumbo nucifera*, *Arundo donax*, and *Acorus calamus* to restore habitats and shelters for riverine animals and amphibians.

3.4 Integrated Spatial Design

Integrating techniques including ecological flood management, constructed wetland design, and habitat restoration with spatial design, an overall plan was generated in which the site was proposed as a floodplain, a series of sponge wetland, and an urban park, providing comprehensive services and meeting the multiple goals in the levels of water safety, water environmental health, water resource, riverine ecosystem, and recreational system (Fig. 7, 8).

3.4.1 An Urban Park Adaptive to Flood

Taking full advantage of the site's topography, a spatial framework of one corridor and three layers was defined to make the site resilient and adaptive to floods.

1) One corridor: an east-west recreational corridor was created throughout the site through the reinforcement and landscape restoration of the existing earth embankments. The elevation varies from 381.30 m to 383.10 m, capable to withstand 20-year flood events.

2) The first layer: the zone of higher elevation (380.00 ~ 383.10 m), where there could withstand 20-year flood events (7,080 m³/s). As the lowest flood-risk zone in the site, this area was designed to provide rich waterfront experiences for local residents through various leisure and recreational places, including a greenway, a waterfront square, a Shaanxi-opera amphitheater, orchards, community gardens, sports grounds and exercise spaces, teahouses, kiosks, etc.

3) The second layer: the zone of medium elevation (380.60 ~ 382.70 m), where there could withstand 10-year flood events (5,910 m³/s). This area consists of subsurface and surface flow wetlands for wastewater purification and flood retention, acting as a buffer between the city and the river and creating spaces for leisure activities like walking, fishing, and picnic in the wetland area.

4) The third layer: the zone of lower elevation (374.00 ~ 381.00 m), with a high flooding risk (being inundated by 5-year flood events or rainfalls). As an area of floodplains, this zone was

7. 总平面图
8. 与洪水相适应的空间设计
9. 生态湿地区在城市与渭河间构建起一道城市海绵，具有雨洪调蓄、废水净化再生的功能，兼顾休闲体验与环境教育。

7. Site plan
8. Flood adaptive spatial design
9. Through combination of spatial design and wetland purification process, the constructed wetlands in the site not only act as an urban sponge of flood management, but also allow for wastewater recycling, leisure and recreational activities, and environmental education.

7
© 一一方国际环境景观

10
© 一方国际环境景观

湿地，最大程度顺应渭河的自然摆动和水位周期性变化。该区域中设置简单石板步道，平日可供市民自由漫步，泛洪时不影响行洪过程。

3.4.2 与净化调节过程相结合的游憩体验

生态湿地区在城市与渭河间构建起一道城市海绵，具有雨洪调蓄、废水净化再生的功能，兼顾休闲体验与环境教育。通过合理设计，将游憩体验空间与湿地净化流程相结合，借助氧化塘、潜流湿地

designed to protect and restore natural wetlands and to adapt to the swing and water level change of Weihe River. Stepping stones were created as paths for visitors to stroll through, while allowing for drawing off of floodwater during a flood.

3.4.2 Recreational System Integrated with Water Purification and Management Functions

Through combination of spatial design and wetland purification process, the constructed wetlands in the site not only act as an urban sponge of flood management, but also allow for wastewater recycling, leisure and recreational activities, and environmental education. Through a series of water purification facilities, including retention ponds, subsurface flow wetlands (3 hm²), surface flow wetlands (5.4 hm²), water quality improving area and water quality stabilizing area, the constructed wetlands can treat about 8,000 m³ wastewater daily on average.

Combining horizontal subsurface flow wetlands and surface flow wetlands and flower fields (*Phragmites australis*, *Acorus calamus*, *Iris tectorum*, *Typha orientalis*, and other plants), together with sightseeing boardwalks and bridges built along the terrain, the site can provide both water treatment and recreational services. Various micro

11
© 一方国际环境景观

- 10,11. 雨季时可被洪水淹没的自然滩地
12. 用净化后的水浇灌的市民菜园
- 10,11. Natural floodplain which can be inundated in rain season.
12. Vegetable gardens irrigated with the water purified by the constructed wetlands

净化区（3hm²）、表流湿地净化区（5.4hm²）、水质提升区、水质稳定区5个环节，平均每日可净化8 000m³由污水处理厂排放的废水。

通过将水平潜流和表流湿地与花田景观结合，种植芦苇、菖蒲、鸢尾（*Iris tectorum*）、香蒲（*Typha orientalis*）等植物，并设置随地势蜿蜒起伏的景观栈道与栈桥，使该区域兼具净化与景观体验功能。水质提升区设计了多个小型景观湿地，其间利用高差设置多级石堰跌水曝氧，并引入鱼类等水生生物以抑制藻类生长，有助于进一步水质提升。水质稳定区被设计为中央景观湿地，休闲步道、亲水平台环绕其间。净化后的水流入亲水体验广场的浅水池中，人们或邻水休憩，或嬉水玩耍。净水还可用于灌溉果园和市民农园，让人们在享受农耕劳作的田园乐趣中体验水的再生价值。游憩体验设计为市民提供了不同深度和类型的参与机会，既有散步、观赏、休憩等基本体验，又有垂钓、野餐、蔬菜种植等可深度参与的自然体验。

3.5 成本效益分析

渭柳湿地公园一期工程于2017年5月建成，并已开展后续绩效评估工作。据初步成本效益评估，项目建设成本（70元/m²）仅为咸阳同等面积普通公园的三分之一，发挥了环境、社会、经济方面的综合效益，基本实现了设计目标。1）在环境效益方面，据监测结果显示总磷（0.12mg/L）、COD（9.7mg/L）、氨氮（0.27mg/L）均达到地表Ⅲ类水标准，较建设前污水处理厂尾水和雨污明渠监测数据，分别实现COD削减59.8%和89.6%、氨氮削减53.4%和98.4%；总磷削减70.7%和96.6%，总氮削减62.8%和79.6%。项目实现每年废水资源化再生240万立方米，达到了10%的污水厂废水再生率目标。公园内不同地区草本群落生物多样性Shannon–Wiener指数提升至1.57~1.91，乔木群落提升至2.11~2.33。2）在社会效益方面，场地从难以进入的荒滩变为具有丰富游憩体验和可深度参与的公园，有益于提升居民的环境教育、审美体验和身心健康。3）在经济效益方面，市民农园、运动场地等服务设施实现了公园的持续性收益，公园亦促进了周边地产的增值。

wetlands were designed in the water quality promoting area, where a water terrace was built for drop-aeration and aquatic organisms like fish can inhibit algae growth, helping maintain the water quality. The water quality stabilizing area was designed as a central landscape wetland surrounded by waterfront trails and platforms. The purified water then flows into the shallow pools of the waterfront square, where visitors can have a rest and children can play with water. The purified water is also used to irrigate orchards and community gardens, encouraging people to enjoy the pastoral experience of farming works.

3.5 Cost-Benefit Evaluation

The first phase project of Weiliu Wetland Park was completed in May 2017 and relevant performance evaluation has been launched. A preliminary cost-benefit evaluation estimates that the average construction cost is about 70 RMB/m², saving over 66% of cost comparing to the same-size non-wetland public parks in Xianyang. The environmental, social, and economic performance of the site has been largely improved: 1) The monitoring results show that the surface water quality on the site meets the Surface Water Class III Standard, the concentrations of TP, COD and ammonia nitrogen are lowered to 0.12 mg/L, 9.7 mg/L, and 0.27 mg/L, respectively. Compared with the sampling results of the water collected from the outlets of the sewage plant and the ditches on the site, the concentration of COD is reduced by 59.8% and 89.6%, ammonia nitrogen reduced by 53.4% and 98.4%, TP reduced by 70.7% and 96.6%, and TN reduced by 62.8% and 79.6%, respectively. The annual waste water treatment capacity is approximately 2.4 million cubic meters, meeting the goal of a 10% wastewater recycling rate. The Shannon-Wiener index on the biodiversity of herb community in the park increases to 1.57 ~ 1.91 and that of arbor community increases to 2.11 ~ 2.33. 2) Through ecological restoration and accessibility improvement, the site has been changed from a wasteland into a destination which provides diverse leisure and recreational experiences and opportunities for public engagement, enhancing citizens’ environmental education and aesthetics, and physical and mental health. 3) The income from the community gardens, sports grounds, and other service facilities ensures the sustainable running of the park; the park also contributes to the price increase of the surrounding real estates.

13 © 一方国际环境景观

4 Conclusion

Site-scale GI design ought to address specific, intricate issues by integrating multiple considerations. At present, though GI design has been widely applied throughout China, few examples can be named which not only respond to specific problems on the site, but also combine engineering techniques with spatial design in order to maximize the comprehensive benefits. Among all the reasons, the lack of multi-disciplinary collaborative design impedes the development of site-scale GI practice. In the Weiliu Wetland Park project, an interdisciplinary collaborative design was explored which is based on the knowledge of hydraulic engineering, environmental science, ecology, and landscape architecture, and closely combines research, engineering

13. 场地原有土堤经改造后形成休闲绿廊，可作为生态护堤抵御20年一遇的洪水。
14. 雨水和废水净化后可供市民亲水嬉水、观赏水景。
13. The earth embankments were transformed as a recreational corridor which is designed to withstand 20-year flood events.
14. Rainwater and sewage is recycled and purified for creating waterfront landscapes where people can play, relax, and enjoy the views.

14 © 一方国际环境景观

4 结语

绿色基础设施场地实践需要解决多重问题，实现多重目标与价值。目前中国虽已广泛开展绿色基础设施实践，但缺乏既可精准地解决具体问题，又能发挥综合效益、兼顾人居环境品质的案例。实践项目的设计过程缺少多专业的紧密协同成为重要掣肘。咸阳渭柳湿地公园项目探索了一套将科学研究、专业技术、空间设计紧密衔接，水利、环境、生态、景观等多学科交叉合作的协同设计模式。其一，需通过科学的监测分析准确诊断问题、细化设计目标、明确具体指标；其二，针对单一问题和单项指标，提出专项工程技术方案；其三，通过空间综合设计统筹应用各专项技术，实现综合目标。

本文亦需指出，绿色基础设施协同设计方法仍有待进一步完善。一是场地尺度设计实践需要与宏观绿色基础设施网络紧密衔接，以实现跨尺度的系统性协同；二是设计过程应加入对方案的成本效益评估，以验证设计是否达到预期指标，评估结果可用于方案的进一步修正。**LAF**

techniques, and spatial design as a whole. The process can be concluded as: first, through on-site investigation and analysis, problems can be accurately identified that informs to generate detailed design objectives and clarify the specific indicators; secondly, special technical solutions are proposed aiming at individual issues; thirdly, all the required engineering techniques are integrated with an overall spatial and environmental design in order to maximize ecological, social, and economic benefits of the project.

It must be pointed out that this method of GI collaborative design should be further improved. First, a site-scale GI design should be integrated into the GI system at a greater scale to enhance the effective connection across scales and to form a systemic ecological framework. Second, a cost-benefit assessment should be considered in the design process to evaluate whether the design meets the expected indicators or not, and the assessment results can help revise or improve the design proposals. **LAF**

REFERENCES

[1]

Luan, B., Chai, M. W., & Wang, X. (2017). Review of Development, Frontiers, and Prospects of Green Infrastructure. *Acta Ecologica Sinica*, 37(15), 1-16.

[2]

Li, F., Wang, R. S., & Zhao, D. (2014). Urban Ecological Infrastructure Based on Ecosystem Services: Status, Problems and Perspectives. *Acta Ecologica Sinica*, 34(1): 190-200.

[3]

Liu, H. L., Li, D. H., & Han, X. L. (2005). Review of Ecological Infrastructure: Concept and Development. *City Planning Review*, 29(9), 70-75.

[4]

Benedict, M. A. (2000). Green infrastructure: A strategic approach to land conservation. Retrieved from <http://www.scopus.com/inward/record.url?eid=2-s2.0-0034458360&partnerID=40&md5=f9cb4f282b5ea12cc62c6fce7bb208a5>

[5]

Benedict, M. A., & McMahon, E. T. (2002). Green Infrastructure: Smart Conservation for the 21st Century. *Renewable Resources Journal*, 20(3), 12-17.

[6]

Benedict, M. A., & McMahon, E. T. (2006). *Green Infrastructure: Linking Landscapes and Communities*. London: Island Press.

[7]

Tzoulas, K., Korpela, K., Venn, S., Yli-Pelkonen, V., Kaźmierczak, A., Niemela, J., & James, P. (2007). Promoting ecosystem and human health in urban areas using Green Infrastructure: A literature review. *Landscape and Urban Planning*, 81(3), 167-178. doi: <http://dx.doi.org/10.1016/j.landurbplan.2007.02.001>

[8]

von Döhren, P., & Haase, D. (2015). Ecosystem disservices research: A review of the state of the art with a focus on cities. *Ecological Indicators*, 52, 490-497. doi:10.1016/j.ecolind.2014.12.027

[9]

Gomez-Baggethun, E., & Barton, D. N. (2013). Classifying and valuing ecosystem services for urban planning. *Ecological Economics*, 86, 235-245.

[10]

Lu, X. L. (2012). Research on collaborative design of public space of urban complex (Master's thesis). Available from CNKI. doi: 10.7666/d.y2154130

[11]

Cai, J. (2005). Discussion on architectural collaborative design (Master's thesis). Available from CNKI.

[12]

She, Y. S. (2017). Collaborative Design and Innovative Management — The Experience of Sponge City Development in the Eastern New District of Wenling City. *Landscape Architecture Frontiers*, 5(1), 56-65.

[13]

Pei, D. (2012). Review of Green Infrastructure Planning Methods. *City Planning Review*, 36(5), 84-90.

[14]

Weber, T. (2003). Maryland's Green Infrastructure Assessment: A Comprehensive Strategy for Land Conservation and Restoration. Maryland: Maryland Department of Natural Resources, Watershed Services Unit, Landscape and Watershed Analysis Division.

[15]

Li, B. (2009). Green Infrastructure and the control of urban sprawl. *Urban Problems*, (1), 86-90.

[16]

Zhai, J. (2012). Coordinative Symbiosis: From Grey Municipal Infrastructure and Green Ecological Infrastructure to Integrate Landscaping Infrastructure. *Planners*, 28(9), 71-74.

[17]

Du, S. Q., & Yu, D. Y. (2010). Urban ecological infrastructure and its construction principles. *Chinese Journal of Ecology*, 29(8), 1646-1654.

[18]

Yu, K. J., Li, D. H., Liu, H. L., & Cheng, J. (2005). Growth Pattern of Taizhou City Based on Ecological Infrastructure: A Negative Approach Physical Urban Planning. *City Planning Review*, 29(9), 76-80, 97-98.

[19]

Yu, K. J., Li, H. L., Li, D. H., Qiao, Q., & Xi, X. S. (2009). National scale ecological security pattern. *Acta Ecologica Sinica*, 29(10), 5163-5175.

[20]

Yu, K. J., Wang, S. S., Li, D. H., & Li, C. B. (2009). The function of ecological security patterns as an urban growth framework in Beijing. *Acta Ecologica Sinica*, 29(3), 1189-1204.

[21]

Meng, Y. X., & Wang, C. (2013). Green System Planning Base On The Green Infrastructural. *Planners*, 29(9), 57-62.

[22]

Fang, J. Y., Wang, X. P., Shen, Z. H., Tang, Z. Y., He, J. S., Yu, D.,... Guo, Z. D. (2009). Methods and protocols for plant community inventory[J]. *Biodiversity Science*, 17(6), 533-548.

[23]

Ministry of Environmental Protection of the People's Republic of China.(2014).Technical Guidelines for Biodiversity Monitoring—large- and Medium- sized Soil Animals. Retrieved from <http://kjs.mep.gov.cn/hjbhbz/bzwb/stzl/201411/W020141106568383958445.pdf>

[24]

Ministry of Environmental Protection of the People's Republic of China. (2002). Discharge Standard of Pollutants for Municipal Wastewater Treatment Plant. Retrieved from <http://kjs.mep.gov.cn/hjbhbz/bzwb/shjbh/swrwpfbz/200307/W020061027518964575034.pdf>

[25]

Kadlec, R. H., & Knight, R. L. (1996). *Treatment Wetlands*. Chelsea: Lewis Publishers.

[26]

Rousseau, D. P. L., Vanrolleghem, P. A., & de Pauw, N. (2004). Model-based design of horizontal subsurface flow constructed treatment wetlands: a review. *Water Research*, 38(6), 1484-1493.

[27]

Yu, K. J., Li, D. H., & Chao, L. M. (2001). Ten Landscape Strategies to Build Urban Ecological Infrastructure. *Planners*, 17(6), 9-13, 17.

[28]

Williamson, K. S. (2003). Growing with Green Infrastructure. Retrieved from http://conservationtools.org/library_items/21/files/16

[29]

Goode, D. (2006). Green Infrastructure — Report to the Royal Commission on Environmental Pollution. Retrieved from <http://www.ukmaburbanforum.co.uk/documents/papers/green-infrastructure-david-goode.pdf>

[30]

European Commission. (2013). *Building a Green Infrastructure for Europe*. Luxembourg: Publications Office of the European Union.

[31]

Royal Commission on Environmental Pollution. (2007). *The Urban Environment: Royal Commission on Environmental Pollution*. The Stationary Office, UK, 218.

[32]

European Environment Agency. (2011). *Green Infrastructure and Territorial Cohesion*. Retrieved from <http://www.eea.europa.eu/publications/>

[33]

He, W., & Liu, B. Y. (2011). Rethinking of Several Issues of Green Infrastructure. *Chinese Landscape Architecture*, 27(1), 88-92.

[34]

Luan, B., Wang, X., Huang, S. H., Shao, W. W., & Chen, J. X. (2017). The Design Exploration of Urban Edible Landscape in China. *Landscape Architecture*, (9), 36-42.

[35]

Ministry of Environmental Protection of the People's Republic of China, & General Administration of Quality Supervision, Inspection and Quarantine of the People's Republic of China. (1995). *Environmental Quality Standard for Soils*. Retrieved from <http://kjs.mep.gov.cn/hjbhbz/bzwb/trhj/trhjzlbz/199603/W020070313485587994018.pdf>

[36]

China National Environmental Monitoring Centre. (1990). *Elements Background Value of China soil*. Beijing: Science China Press.

景观设计学 / 论文 LANDSCAPE ARCHITECTURE FRONTIERS / PAPERS

043