

Ziru LI, Zhaobin XU, Tao ZHANG, Xinbo YUAN, Zhonghe JIN, 2026. High-precision temperature prediction for atmospheric refractivity correction using Kalman spatiotemporal data fusion. *ENGINEERING Inform Technol Electron Eng*, 27(5):260005. <https://doi.org/10.1631/ENG.ITEE.2026.0005>

High-precision temperature prediction for atmospheric refractivity correction using Kalman spatiotemporal data fusion

Key words: Temperature prediction; Kalman filter expanded fusion (KFEF); Atmospheric refraction correction; Absolute distance measurement; Generalized regression neural network (GRNN) optimization

Corresponding author: Zhaobin XU

E-mail: zjuxzb@zju.edu.cn

 ORCID: <https://orcid.org/0000-0003-3059-8974>

Motivation

1. Atmospheric refraction error is the key limiting factor for high-precision absolute distance measurement and positioning. Temperature plays a dominant role in computing the atmospheric refractive index.
2. In complex and dynamic outdoor environments, limited sensor deployment and environmental nonstationarity make it extremely difficult to obtain accurate temperature fields along the ranging path.

Main idea

1. Propose Kalman filter expanded fusion (KFEF) algorithm for high-precision temperature prediction in atmospheric refractivity correction.
2. Integrate the advantages of generalized regression neural network (GRNN) (temporal prediction) and Kriging (spatial interpolation) based on the Kalman filter framework.
3. Achieve dynamic prediction and high-accuracy reconstruction of spatiotemporal temperature fields, adapting to sparse sensors and complex outdoor environments.

KFEF method

1. Dynamic GRNN optimization algorithm based on simulated annealing (GRNN-SA): Proposes a simulated annealing-based optimization strategy for GRNN smoothing factor selection.
2. Adaptive Kalman filtering with spatial correlation modeling: Constructs a state transition matrix using Kriging variogram theory and dynamically updates measurement noise covariance through GRNN prediction residuals.
3. Fixed-interval interpolation enhancement: Introduces a data augmentation strategy that combines GRNN prediction and Kriging interpolation to expand sparse sensor observations.

Major results

1. Test results of our model and related methods in simulations

Table 4 Three error evaluation metrics between the interpolation results of five methods and the actual temperature in simulations

Method	RMSE	MAE	MAPE
RBF	0.065	0.044	0.17
STK	0.038	0.035	0.14
GP	0.037	0.034	0.13
KFF	0.036	0.032	0.12
KFEF	0.025	0.021	0.09

Major results (Cont'd)

2. Test results of our model and related methods in the indoor experiment

Table 6 Three error evaluation metrics between the interpolation results of five methods and the actual temperature in the indoor experiment

Method	RMSE	MAE	MAPE
RBF	0.350	0.312	1.49
STK	0.195	0.164	0.73
GP	0.193	0.154	0.72
KFF	0.190	0.148	0.70
KFEF	0.147	0.121	0.57

Major results (Cont'd)

3. Test results of our model and related methods in the outdoor experiment

Table 8 Comparison of temperature prediction STD among four methods in the outdoor experiment

Distance (m)	Temperature STD (°C)			
	RBF	GP	STK	KFEF
24	0.19	0.12	0.13	0.10
48	0.28	0.21	0.22	0.15
72	0.31	0.23	0.24	0.17
168	0.38	0.29	0.31	0.20
312	0.40	0.34	0.35	0.22
432	0.43	0.37	0.38	0.24
600	0.45	0.39	0.40	0.25
792	0.49	0.36	0.37	0.26
1008	0.51	0.45	0.48	0.27

Conclusions

1. We propose KFEF algorithm integrating GRNN-SA, Kriging interpolation, and adaptive Kalman filter for atmospheric refractivity correction under sparse sensor observations.
2. Simulations verify that KFEF achieves a 61.54% reduction in root mean square error (RMSE) compared with the radial basis function (RBF). KFEF lowers the microwave ranging error from millimeter to micrometer level for kilometer-scale ranging in the outdoor experiment.
3. The spatiotemporal fusion framework is general and scalable for various temperature field tasks, and future work will enhance its adaptability to nonstationary atmospheric environments.



Ziru LI received the Bachelor's degree in measurement and control technology and instrument in Taiyuan University of Technology, Taiyuan, China in 2023. She is currently pursuing the Ph.D. degree at the School of Aeronautics and Astronautics, Zhejiang University, Hangzhou, China. Her research interests include absolute distance measurement and atmospheric refraction.



Zhaobin XU received the Bachelor's and Ph.D. degrees in electronic science and technology from Zhejiang University, Hangzhou, China, in 2008 and 2013, respectively. He is currently an associate professor at the School of Aeronautics and Astronautics, Zhejiang University, Hangzhou, China. His research interests include absolute distance measurement, high-precision inter satellite measurement, and navigation of micro-nano satellites.



Tao ZHANG received the Bachelor's degree in electronic information engineering from Northeastern University at Qinhuangdao, China, in 2021. He is currently pursuing the Ph.D. degree at School of Aeronautics and Astronautics, Zhejiang University, Hangzhou, China. His research interests include radio ranging.



Zhonghe Jin received the Ph.D. degree in microelectronics and solid state electronics in Zhejiang University in 1998. He is currently a professor at School of Aeronautics and Astronautics, Zhejiang University, Hangzhou, China. He is also a recipient of National Science Fund for Distinguished Young Scholars (2015). He has published more than 200 academic papers and has been granted over 90 invention patents. His research achievements have won the second prize of Science Research Famous Achievement Award in Science and Technology—Natural Science Award and the first prize of Zhejiang Provincial Science and Technology Award. As an expert in the National Manned Space Program Expert Group, he has participated in key aerospace technology research.